

Color Fast® Tile and Grout Caulk

1. Product Description

Colorfast Tile and Grout Caulk is a high grade siliconized acrylic that is designed for interior and exterior applications. It is available in both sanded and non-sanded. Comes in most grout manufacturer colors with the ability to color match. Meets ASTM C834 Type OP, Grade 0°C

2. Features and Benefits

- Water clean up
- Paintable
- Mold & mildew resistant
- Tube comes with cap
- Easy to tool
- Flexible

3. Uses

- For gaps up to 1/4" (6 mm)
- Flexible sealant for horizontal and vertical substrates
- Tubs, sinks, showers, countertops, ceramic tile floors
- Bath, kitchen and other fixtures
- Interior and exterior

4. Limitations

- Max joint width 1/4" (6 mm)
- Not for constant water immersion
- Not rated for expansion joints, use Ultra Performance Caulking
- Not rated for traffic or abrasion
- Not for structural glazing
- Test on small area when working with porous materials to verify results are non staining

5. Packaging

Available in 10.3 oz. (310 ml) and 32 oz. (950 ml)

6. Shelf Life

Two years in original unopened tube

7. Cautions

Consult SDS

8. Cleaning and Maintenance

Fully cured joint should be cleaned with a neutral pH cleaner, such as ColorFast Citrus Cleaner

9. Technical Specifications

Tack free time	30 minutes (Depending on temp and humidity)
Slump	< 0.15 inch (3.80 mm)
Shrinkage	< 30% max
Set time	24 -72 Hours
Full cure	3 - 5 days
Freeze thaw stability	3 cycles
Stain resistance	Good
Crack resistance	Good
Mildew resistance	Good
Application temperature	40°F (4°C) - 90°F (32°C)

10. Preparation

Clean area of any dust, dirt, mildew, oil and other foreign substance. For existing applications remove all old caulking before applying new caulk, clean area with a mild solution of bleach and water.

11. Application

Make sure area is dry before applying caulk. Remove cap and cut spout to desired bead thickness. Apply Caulk when temperature is above 40°F. Tool Caulking within 10 minutes of application using a wet finger or damp rag. Excess may be cleaned up with a damp cloth before caulk begins to skin over.

12. Cure Time

Caulk is fully cured in 3-5 days depending on temperature, humidity and thickness of application.

13. Technical Service

For technical assistance contact ColorFast Technical Services at 1-800-400-2488 or visit www.colorfastind.com

